

# PRODUCT SUBMITTAL

WIRE-BOND

## #3200 Panel Anchor



### MATERIAL CONFORMANCE

### SIZES / FINISHES

**SHEET METAL** - (Carbon Steel) ASTM A1008 / A1008M

**Hot Dip Galvanized after fabrication / Zinc Coating**  
ASTM A153 / A153M-B2 (1.50 oz per sq ft)

**Stainless Steel** ASTM 580 / ASTM 580M Type 304  
(Type 316 available on special order)



**Recycled Content:**  
Mill Galvanized & Hot Dipped,  
82.8% Post-Consumer  
17% Post Industrial / Pre-Consumer,

Stainless Steel,  
97% Pre-Consumer  
V O C Content - 0%

#### **PANEL ANCHOR:**

Provides support to standard glass block panels.  
Spaced and installed according to specification.

**DIMENSIONS:** 20 gauge perforated strips, 1-3/4" x 24".

#### **FINISHES:**

Hot Dip Galvanized

Stainless Steel

Corporate Office: 400 Rountree Rd Charlotte, NC 28217  
TEL: (800) 849-6722 FAX: (704) 525-3761  
Mailing Address: P.O. Box 240988 Charlotte, NC 28224



[www.wirebond.com](http://www.wirebond.com)

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113  
TEL: (800) 441-8359 FAX: (901) 775-9449  
Mailing Address: P.O. Box 13124 Memphis, TN 38113